

# Smart Battery Charger



<b>2.0L</b> Engine size	<b>6/12V</b> Voltage	 Battery type	 Start/stop	 Weatherproof	 Current
----------------------------	-------------------------	------------------	----------------	------------------	-------------



- **Multi-stage smart charge cycle ium Cobalt LiCoO2 jump starter**  
Repairs and protects vehicle battery
- **Charges twice as fast as a standard charger**
- **Multi-stage charging cycle**  
To repair damage and protect against overcharging.
- **Includes winter charge mode**  
For effective charging in cold weather
- **Ideal for START/STOP vehicles**
- **Suitable for lead acid, gel, calcium, EFB and AGM batteries**
- **Rated IP65**  
Making it weatherproof
- **LCD screen**  
To make selecting the correct program simple

## Specifications

Product Code	RSC404 (UK), RESC404 (Euro)
Battery Capacity (Charging)	90Ah
Battery Capacity (Maintenance)	140Ah
Nominal Voltage	6V/12V
Battery Clamps	1.5M
Cable Length	1.5M
Winter Charging Mode	✓
Battery Repair Function	✓
Maintenance Mode Setting	✓
Battery Clamps Only	✓
Weight	0.65g
Pack Dimensions	H136 x W255 x D58mm
Case Quantity	4
Barcode	5055175241739 (UK) 5055175243405 (Euro)

Ring Automotive Limited . Gelderd Road, Leeds, LS12 6NA United Kingdom  
 Telephone +44 (0)113 213 2000 . Fax +44 (0)113 231 0266  
 Email autosales@ringautomotive.com . www.ringautomotive.com

/ringautomotive